

DECLARATION OF PERFORMANCE N. CPR-TR/0033

- 1) Unique identification code of the product-type: **NIVOPLAN PLUS**
- 2) Intended uses: **Cementitious screed material for internal use in floor construction**
- 3) Manufacturer: **Mapei Yapı Kimyasalları İnş. San. ve Tic. A.Ş. Polatlı Organize Sanayi Bölgesi
209. Cad. No: 7 Polatlı/ANKARA**
- 4) Systems of AVCP: **System 4**
- 5) Harmonized standards: **EN 13813:2002**
 Notified bodies: **No task for the notified body**
- 6) Performances declared:

Essential characteristics	Performances
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C20
Flexural strength:	F5
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD
Reaction to fire:	Class A1_{fl}

- 7) Appropriate Technical Documentation: reaction to fire class declared without the need for testing according to the Decision of the Commission 96/603/EC.
 Organic material < 20% by weight Maximum layer thickness 20 mm.
- 8) REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance

The performance of the product identified above is in conformity with the set of declared performances.
This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Selman TARMUR – General Manager



ANKARA, 16/01/2020

DoP in Pdf format are available in the Mapei website.

<i>Revision 0 notes:</i>	<i>The first issue</i>
--------------------------	------------------------

NIVOPLAN PLUS
CE MARKING
Annex to DoP N. CPR-TR/0033



	 MAPEI YAPI KİMYASALLARI İNŞ. SAN. ve TİC. A.Ş. POLATLI OSB 209. CAD. NO:7 POLATLI/ANKARA (TÜRKİYE)
15 CPR-TR/0033 EN 13813 NIVOPLAN PLUS <i>Cementitious screed material for internal use in floor construction</i>	
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C20
Flexural strength:	F5
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD
Reaction to fire:	Class A1fl

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD values can be omitted by the CE marking
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.