

DECLARATION OF PERFORMANCE N. CPR-NO1/0450

- 1) Unique identification code of the product-type: **Ultratop N Industrial**
- 2) Intended uses: **Cementitious screed material for internal use**
- 3) Manufacturer: **MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua – Norway - www.mapei.no**
- 4) Systems of AVCP: **System 4**
- 5) Harmonized standards: **EN 13813:2002**

Notified bodies: **No tasks for notified body**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class A2 _{fl-s1}
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C40
Flexural strenght:	F10
Wear resistance:	A9
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

- 7) Appropriate Technical Documentation: **Not applicable**
- 8) REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – Regional Manager**

Sagstua, 03/05/2022

.....
DoP in Pdf format are available in the Mapei website.

Revision 0 notes:	New declaration
-------------------	-----------------

Ultratop N Industrial
CE MARKING
Annex to DoP N. CPR-NO1/0450



	 Valsetvegen 6 – 2120 Sagstua (Norway) www.mapei.no
22 CPR-NO1/0450 EN 13813 Ultratop N Industrial <i>Cementitious screed material for internal use</i>	
Reaction to fire:	Class A2fl-s1
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C40
Flexural strenght:	F10
Wear resistance:	A9
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *NPD (No Performance Determined) values can be omitted by the CE marking*
- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*